GC1015





**Philips Domestic Appliances and Personal Care** 

# Manual

## **PRODUCT INFORMATION**

- Colour white/green
- Aluminium soleplate
- Tank capacity (150 ml)
- Integrated calc clean
- Steam rate (15 g/min)
- Spray feature

# **Safety Information**

- This product meets the requirements regarding interference suppression on radio and TV.
- After the product has been repaired, it should function properly and has to meet the safety requirements and legal regulations set by the related countries.

### **TECHNICAL INFORMATION**

- Voltage : 220 ~ 240 V

: 50 ~ 60 Hz - Frequency

- Power consumption: 1200 - 1450 W

- Dimension (F-box) : 272 mm x 107 mm x 140 mm

- Weight (Product) : 870 grams

- Water advice : Suitable for tap water use.

> However if the tap water in your area is very hard, we advise you to mix it with a equal portion of distilled water or to use distilled

water only.

# Soleplate

The Aluminium soleplate used is smooth and corrosion free which treats fabrics gently.

#### Calc clean

The integrated Calc clean function ensure a longer lifetime using normal tap water by removing the scale out of the steam chamber.

Published by Philips Domestic Appliances and Personal Care

© Copyright reserved

Subject to modification



DISASSEMBLY ADVICE GC1015

**BACKPLATE 3** 

**LAMP ASSY 8** 

**SWIVEL 9** 

**CORDSET 10** 

**INLAY 5** 

Remove Screw A 1x
Remove BACKPLATE 3
Remove LAMP ASSY 8
Remove SWIVEL 9
Remove CORD SET 10
Remove DOSING ASSY 1

Remove Screw B 1x Remove INLAY 5 Remove PUMP ASSY 7 DIAL 2

**TANK SET 6** 

THERMOSTAT BUSH II


**COVER 12** 

**ISOLATION STUD 13** 

**COVER SEAL 14** 

**SOLEPLATE ASSY 16** 

Remove DIAL 2



Remove DOSING ASSY 1

Remove SPRAY KNOB 4

Remove Screw B 1x

Remove INLAY 5

Remove PUMP ASSY 7

Remove Screw C 3x

Remove TANK SET 6

Remove THERMOSTAT BUSH 11

Remove Screw D 3x

Remove COVER 12

Remove ISOLATION STUD 13

Remove COVER SEAL 14

Remove SOLEPLATE ASSY 16


# **REPAIR INSTRUCTIONS**

- In case of any defect in the thermostat, the complete soleplate has to be replaced.
- No information about the type number has been stamped into the type plate. When replacing the type plate, engrave at least type number and voltage onto the type plate with a tool.

# **OPTIONAL** (accessories)

- No specific issues

Pos	Service code	Description
1	4239 021 14550	Dosing assembly (non extra steam)
2	4239 021 14540	Dial printed (English)
3	4239 015 35900	Back plate - South Africa
	4239 015 36300	Back plate - Taiwan
4	4239 026 13260	Spray knob
5	4239 026 12110	Inlay (with spray feature)
6	4239 022 53630	Tank set (with spray feature)
7	4822 360 10416	Pump assembly
8	4239 021 14520	Lamp assembly
9	4822 325 10226	Swivel
10	4239 000 07210	Cord set - South Africa
	4239 000 07320	Cord set - Middle East, Africa
	4239 000 07150	Cord set - Taiwan
11	4239 026 12830	Thermostat bush
	4239 015 98410	Thermostat bush - Middle East, Africa
12	4239 026 12070	Cover
13	4822 532 12722	Isolation stud
14	4822 441 81097	Cover seal
15	4239 015 54210	Tank seal
16	4239 021 14460	Soleplate assembly (220-240V) South Africa
	4239 021 17720	Soleplate assembly (120V) Taiwan



GC1015

