## 7705

- 300V, 2A capacity
- Two 50-pin female Dsubconnectors are standard for secure hook-up and quick teardown
- Relay closures stored in onboard memory

### **Ordering Information**

7705 40-Ch, Single-Pole, Control Module


### Accessories Supplied

Two mating connectors with solder cup (Model 7788)

# 40-Channel Single-Pole Control Module



The Model 7705 plug-in module offers 40 channels of independent switching. These channels are designed to control power to the DUT and switching loads. They can also directly control light indicators, relays, etc.



### INPUTS

MAXIMUM SIGNAL LEVEL: 300VDC or rms, 2A switched, 60W (DC, resistive), 125VA (AC, resistive).

CONTACT LIFE: Cold Switching: 10<sup>8</sup> closures.

At Maximum Signal Levels: 10<sup>5</sup> closures.

CHANNEL RESISTANCE (per conductor):  $<1\Omega$ . CONTACT POTENTIAL:  $\le 4\mu V$  per contact.

OFFSET CURRENT: <100pA.

ACTUATION TIME: 3ms.

ISOLATION: Channel to Channel:  $>10^{9}\Omega$ , <50pF. Common Mode:  $>10^{9}\Omega$ , <100pF.

CROSSTALK (1MHz,  $50\Omega$  load): <-35dB.

INSERTION LOSS (50 $\Omega$  source, 50 $\Omega$  load): <0.3dB below 1MHz, <3dB below 10MHz.

COMMON MODE VOLTAGE: 300V between any terminal and

chassis.

### GENERAL

RELAY SWITCH CONFIGURATION: 40 independent channels of 1-pole switching. Isolated from internal DMM.

CONTACT CONFIGURATION: 1 pole Form A.

RELAY TYPE: Latching electromechanical.

CONNECTOR TYPE: Two 50-pin female D-sub connectors.

FIRMWARE: Specified for Model 2700 rev. A01, 2701 rev. A01, and 2750 rev. A01 or higher.

ENVIRONM ENTAL

**OPERATING ENVIRONMENT:** Specified for 0°C to 50°C. Specified to 80% R.H. at 35°C.

STORAGE ENVIRONMENT: -25°C to 65°C.

WEIGHT: 0.45kg (1 lb).

### **ACCESSORIES AVAILABLE**

7705-MTC-2 50 Pin Male to Female DSUB Cable, 2m (6.6 ft).

1.888.KEITHLEY (U.S. only)

www.keithley.com

