

HVL-F42AM

SERVICE MANUAL

Ver 1.0 2008.02



*US Model
Canadian Model
AEP Model
Chinese Model
E Model*

SPECIFICATIONS

FEATURES

Guide number

Normal flash (ISO100)

Flash Coverage Setting (mm)		16*	24	28	35	50	70	105
GN	Manual flash/ 35mm-format	13	23	23	25	30	35	42
	APS-C format	13	25	26	30	35	38	42

* When the wide panel is attached

Frequency/Repetition

	Alkaline	Nickel hydride (2500 mAh)
Frequency (sec)	0.1 - 3.7	0.1 - 2.7
Repetition (times)	Approx. 180 or more	Approx. 260 or more

- Repetition is the approximate number of times that are possible before a new battery is completely dead.

Continuous flash performance	40 flashes at 5 flashes per second (Normal flash, light level 1/32, 105 mm, nickel-metal hydride battery)
AF illuminator	Autoflash at low contrast and low brightness Operating range (with a 50 mm lens attached to DSLR-A700) Central area: 0.5 m to 6 m Peripheral areas : 0.5 m to 3 m
Flash control	Flash control using pre-flash, TTL direct metering
Dimension (Approx.)	W 75 × H 123 × D 100 mm (3 × 4 7/8 × 4 inches)
Mass (Approx.)	340 g (12 oz) (excluding the batteries)
Recommended batteries	AA-size alkaline batteries AA-size rechargeable nickel-metal hydride batteries
Included items	Flash unit (1), Mini-stand (1), Case (1), Set of printed documentation

Functions in these operating instructions depend on testing conditions at our firm.
Design and specifications are subject to change without notice.

- A compact flash that provides a flash output with a maximum guide number 42 (105 mm position, ISO 100 • m).
- Can be used with compatible lenses to enable ADI (Advanced Distance Integration) flash metering, which is not affected by the reflection rate of the background or subject.
- Enables High-speed Sync.
- Provides many functions such as bounce flash, manual flash, etc.
- This flash unit supports flash coverage to a focal length of 16mm by using the built-in wide panel when the flash is triggered.
- Corrects the white balance automatically using the color temperature information.*
- Adjusts the optimum flash coverage according to the image sensor size of the camera.*

* When Sony digital single-lens reflex camera (other than the DSLR-A100) is used.

FLASH

SONY®

SECTION 1 EXPLODED VIEWS

NOTE:

- -XX and -X mean standardized parts, so they may have some difference from the original one.
- Items marked "*" are not stocked since they are seldom required for routine service. Some delay should be anticipated when ordering these items.
- The mechanical parts with no reference number in the exploded views are not supplied.




Ref. No.	Part No.	Description
1	X-2189-011-1	MAIN UNIT
2	X-2189-012-1	LID SET, BATTERY
3	X-2189-184-1	FOOT UNIT, SHOE
4	2-693-229-01	SCREW

SECTION 2 SUPPLIED ACCESSORIES


- Abbreviation

CH: Chinese model
CND: Canadian model

Checking Supplied Accessories



Case
3-291-967-01



Mini-stand
2-691-857-01

Ref. No.	Part No.	Description
3-285-951-01		MANUAL, INSTRUCTION (JAPANESE, ENGLISH, FRENCH) (US, CND)
3-285-951-11		MANUAL, INSTRUCTION (ENGLISH, FRENCH, GERMAN, ITALIAN, DUTCH) (AEP)
3-285-951-21		MANUAL, INSTRUCTION (ENGLISH, PORTUGUESES, SPANISH, SWEDISH, RUSSIAN) (AEP)
3-285-951-31		MANUAL, INSTRUCTION (ENGLISH, ARABIC, TRADITIONAL CHINESE, SIMPLIFIED CHINESE, KOREAN) (E, CH)

Revision History

Ver.	Date	History	Contents	S.M. Rev. issued
1.0	2008.02	Official Release	—	—